

VENT-AXIA LO CARBON WALL/CEILING MOUNTED FANS

SILHOUETTE® 150

Vent-Axia Lo-Carbon long life motors last considerably longer than conventional motors whilst delivering up to 67% energy savings. The extended life of Lo-Carbon fans is due to a new generation of high quality ball bearing motors.

With a slim profile of only 19mm, Silhouette blends in with the wall surface to provide an unobtrusive installation. Silhouette can be ceiling or wall mounted and connected to an appropriate duct run to exhaust outside.

Models include 2 speeds selectable at installation to customise the fan to each application and come complete with a blue LED to indicate operation.

- 19mm stylish low profile grille.
- Downstream airflow guide vanes for improved pressure development.
- 1 of 2 speeds selectable at installation.
- High quality ball bearing motors.
- Modern aesthetics, includes blue LED “on light”.
- Fan IPX4 rated.
- 5 Year Warranty.



PERFORMANCE

Size (mm)	Model	Description & Switching	Extract Performance*		Watts (W)	Sound dB(A) @3m	Order Code
			(m³/hr)	(l/s)			
150	LCS150B	Lo-Carbon Wall/Ceiling Silhouette Standard	165	46	5	35	FAN2213
			241	67	8.2	43	
150	LCS150T	Lo-Carbon Wall/Ceiling Silhouette Timer	165	46	5	35	FAN2214
			241	67	8.2	43	

* 1 of 2 speeds selectable at installation

WATTAGE COMPARISON

Size (mm)	Model	Description	Wattage
150	XFLP150	Manrose Pro-Series Wall/Ceiling Fan	25W
150	LCS150	Vent-Axia Lo-Carbon Wall/Ceiling Fan	8.2W
		Energy Savings	16.8W

Switching Options

1. Standard - Operates from remote switch (not supplied).
2. Timer - Fan operates from a switch and continues to run for a preset time after switching off - adjustable 1-20 minutes.

Requires three wires: permanent phase, switched phase, neutral.

NOTE: All fan flow rates quoted are free air delivery.