

Inline Extraction Fan Kits with Halogen Lamp

These high efficiency inline fans are designed to provide higher levels of extraction for larger bathrooms and the halogen lamp adds light directly above your steam source (e.g. shower or bath). Mixed flow fans provide users with a two fan speed option. 5 year warranty.

Classic Standard Profile	Duct (mm)	Fan Type	Max. Fan Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Specific Fan Power (W/l/s)	Interior Grille	Exterior Grille	Switching	Model	Order Code
					(l/s)	(m³/hr)						
	150	EC Axial	18	91	105	380	0.17	Round White	Eggcrate White	Standard	EL150S	FAN0803
										Timer	EL150T	FAN0804
	125	Axial	20	35	36	130	0.56	Round White	Eggcrate White	Standard	EL125S	FAN2037
										Timer	EL125T	FAN2038
	100	Centrifugal	20	120	31	110	0.65	Round White	Eggcrate White	Standard	EL100S	FAN0420
										Timer	EL100T	FAN0438

Note: Installed system performance is always influenced by duct length and layout

Switching Options

Standard Remote switch (not supplied).
Timer Remote switch (not supplied). Fan continues operating for preset time after switching off. 150mm models include fixed 7 minute timer. 125mm and 100mm model timers are 1-20 minute adjustable and require permanent and switched phase.

Accessories


Diffuser with Halogen Lamp (12V 50W)	Model	White
	EL150	DCT1169
	EL100	DCT0360

Inline Extraction Fan Kits with Halogen Lamp


Dimensions (mm)

Model	Diffuser Cut-Out	A	B	C	D	E	F	G	H
EL150	165	200	143	170	185	200	200	74	148
EL125	145	125	155	125	195	155	170	74	118
EL100	115	130	155	90	100	27	140	74	98


Note: Diffuser cut-out size is a nominal diameter for a circular cut-out.




EL150



EL125



EL100



Diffuser

Technical

Model	EL150	EL125	EL100
Supply	220-240V AC, 50Hz		
Halogen Lamp	12V 50W		
Total Wattage	68W	70W	70W
Sound Level	38 dB(A)	41 dB(A)	45 dB(A)
Max. Operating Temp	45°C	40°C	40°C
IP Rating	IP44	IPX4	IPX4
Duct	5m Flexible PVC	4m Flexible PVC	3m Flexible PVC