


Wall/Ceiling Fans - Eco

Eco fans deliver up to 67% energy savings and fan life is extended is due to high quality ball bearing motors.

With a slim 19mm profile, these axial fans blend in with the wall or ceiling surface to provide an unobtrusive installation and can be connected to an appropriate duct run to exhaust outside.

Models include 2 speeds selectable at installation to customise the fan to each application and come complete with a blue LED to indicate operation.

Classic ECO	Duct (mm)	Max. Fan Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Specific Fan Power (W/l/s)	Sound dB(A)	Switching	Model	Order Code
				(l/s)	(m ³ /hr)					
	150	5	20	46	165	0.11	35	Timer	LCS150T	FAN2214
		8.2	32	67	241	0.12	43			

* 1 of 2 speeds selectable at installation

- 19mm stylish low profile grille
- Downstream airflow guide vanes for improved pressure development
- 1 of 2 speeds selectable at installation
- High quality ball bearing motors
- Modern aesthetics, includes blue LED "on light"

Switching Options

Standard Remote switch (not supplied).

Timer Remote switch (not supplied). Fan continues operating for preset time (1-20 minute adjustable) after switching off. Permanent phase, switched phase and neutral required.

Fan Wattage Comparison

Duct	Fan	Model	Watts
150mm	Manrose Pro-Series Wall/Ceiling Fan	XFLP150	25.0
	Eco Wall/Ceiling Fan	LCS150	8.2
	Energy Saving		16.8

Technical

Supply	220-240V AC, 50Hz
IP Rating	IPX4
Warranty	5 years