

Wall/Ceiling Fans - Standard

These fans are designed for easy installation and efficient operation. 5 year warranty.

| Pro-Series Low Profile | Duct (mm) | Fan Type | Max. Fan Watts (W) | Max. Fan Pressure (Pa) | Free Air Fan Performance | | Specific Fan Power (W/l/s) | Sound dB(A) | Fascia | Switching | Model | Order Code |
|--|--------------|-------------|-----------------------------|---------------------------------|-----------------------------|----------------------|-------------------------------------|----------------|--------|-----------|-----------|---------------|
| | | | | | (l/s) | (m ³ /hr) | | | | | | |
|  | 150 | Axial | 20 | 60 | 101 | 364 | 0.20 | 40 | Square | Standard | XFLP150SS | FAN0594 |
| | | | | | | | | | Round | Standard | XFLP150CS | FAN0609 |
| | | | | | | | | | Square | Timer | XFLP150ST | FAN0595 |
| | 125 | Axial | 20 | 35 | 36 | 130 | 0.56 | 41 | Round | Timer | XFLP150CT | FAN0610 |
| | | | | | | | | | Square | Standard | XFLP125SS | FAN0589 |
| | | | | | | | | | Round | Standard | XFLP125CS | FAN0604 |
| | | | | | | | | Square | Timer | XFLP125ST | FAN0590 | |
| | | | | | | | | Round | Timer | XFLP125CT | FAN0605 | |

| Classic Standard Profile | Duct (mm) | Fan Type | Max. Fan Watts (W) | Max. Fan Pressure (Pa) | Free Air Fan Performance | | Specific Fan Power (W/l/s) | Sound dB(A) | Fascia | Switching | Model | Order Code |
|---|--------------|-------------|-----------------------------|---------------------------------|-----------------------------|----------------------|-------------------------------------|----------------|-----------|-----------|----------|---------------|
| | | | | | (l/s) | (m ³ /hr) | | | | | | |
|  | 300 | Axial | 82 | 60 | 306 | 1100 | 0.27 | 60 | Square | Standard | XFS300S | FAN2040 |
| | 230 | Axial | 45 | 50 | 152 | 550 | 0.30 | 50 | Square | Standard | XFS230S | FAN0374 |
|  | 150 | Axial | 25 | 60 | 101 | 364 | 0.25 | 40 | Square | Standard | XF150S | FAN0120 |
| | | | | | | | | | | Pull Cord | XF150P | FAN0126 |
| | | | | | | | | | | Timer | XF150T | FAN0127 |
| | | | | | | | | | | PIR | XF150PIR | FAN0124 |
| 125 | Axial | 20 | 35 | 36 | 130 | 0.56 | 41 | Square | Standard | XF125S | FAN0072 | |
| | | | | | | | | | Pull Cord | XF125P | FAN0074 | |
| | | | | | | | | | Timer | XF125T | FAN0075 | |
| | | | | | | | | | Standard | XF100S | FAN0046 | |
| 100 | Axial | 20 | 20 | 23 | 85 | 0.87 | 41 | Square | Pull Cord | XF100P | FAN0047 | |
| | | | | | | | | | Timer | XF100T | FAN0048 | |

Note: Installed system performance is always influenced by duct length and layout

Switching Options


Standard Remote switch (not supplied).

Timer Remote switch (not supplied). Fan continues operating for preset time after switching off.

All timers are 1-20 minute adjustable and require permanent and switched phase.

Pull Cord Integral part of fan.

Accessories


| Fascia | Model | Duct | Round | | Square | | |
|--|-------|-------|---------|---------|---------|--------------|---------|
| | | | White | Chrome | White | Satin Silver | Chrome |
|  | XFLP | 150mm | FAN0750 | - | FAN0749 | FAN2071 | FAN0598 |
| | | 125mm | FAN0748 | FAN0757 | FAN0747 | FAN2068 | FAN0755 |

Wall/Ceiling Fans - Standard


Dimensions (mm)

| Model | Cut-Out Size | A | B | C | D | E |
|-----------------|--------------|-----|-----|-----|-----|-----|
| XFLP150S | 173 | 191 | 10 | 122 | 150 | - |
| XLFP150C | 173 | 198 | 10 | 122 | 150 | - |
| XLFP125S | 140 | 161 | 10 | 122 | 118 | - |
| XLFP125C | 140 | 165 | 10 | 122 | 118 | - |
| XFS300 | 310 | 362 | 156 | 81 | 75 | 300 |
| XFS230 | 265 | 286 | 141 | 75 | 66 | 230 |
| XF150 | 160 | 200 | 27 | 74 | 148 | - |
| XF150PIR | 160 | 200 | 55 | 90 | 200 | - |
| XF125 | 140 | 168 | 27 | 74 | 118 | - |
| XF100 | 112 | 155 | 27 | 74 | 98 | - |


Please note: Fan cut-out size is a nominal diameter.




XFLP S



XLFP C



XFS



XF

Technical

| | |
|----------------------------|-------------------|
| Supply | 220-240V AC, 50Hz |
| Max. Operating Temp | 50°C |
| IP Rating | IPX4 |