










Ceiling Extraction Fans – Centrifugal

Manrose CONTOUR fans deliver simple compliance with current New Zealand Building Code G4/AS1 mandatory mechanical extract ventilation system requirements. As well as providing application room specific performance, Contour **Toilet**, **Bathroom** and **Kitchen & Laundry** fans have a comprehensive range of stylish, interchangeable fascia to choose from.

CONTOUR Toilet Fan	Duct (mm)	Fan Type	Max. Fan Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Specific Fan Power (W/l/s)	Sound dB(A)	Fascia	Switching	Order Code
					(l/s)	(m³/hr)					
	100	Centrifugal	30	93	49	175	0.61	38	Range Selection	Standard	FAN7030
	150	Centrifugal	45	147	77	276	0.58	40	Range Selection	Standard	FAN7031
	150	Centrifugal	50	210	105	378	0.48	42	Range Selection	Standard	FAN7032
	150	Centrifugal	106	220	153	550	0.69	42	Round White	Standard	FAN7033
									Square White	Standard	FAN7034

- Fitted lead and plug
- Integrated backdraught shutter
- Deep spigot for easy duct connection
- Swing-out arms for easy installation


Fascia Selections

Fan	Round				Square			
	White	Black	LED White	LED Black	White	Black	LED White	LED Black
								
Toilet	DCT4702	DCT4503	DCT4706	DCT4507	DCT4504	DCT4505	DCT4508	DCT4509
Bathroom	DCT4710	DCT4511	DCT4714	DCT4515	DCT4712	DCT4513	DCT4516	DCT4517
Kitchen and Laundry								

Ceiling Extraction Fans – Centrifugal

Dimensions (mm)

Model	A	B (cut-out size)	C (fascia size)	D
Toilet	170	240	272	100
Bathroom	197	296	328	150
Kitchen and Laundry	197	296	328	150
High Steam Area	197	296	326	150



Technical

Model	Toilet	Bathroom	Kitchen and Laundry	High Steam Area
Supply	220-240V AC, 50Hz			
Max. Operating Temp	40°C			
Tri-Colour LED Fascia - Round	(W) 11 (lm) 932 / 1054 / 1046 (K) 3000K / 4000K / 6000K	16 1294 / 1446 / 1443 3000K / 4000K / 6000K	- -	- -
Tri-Colour LED Fascia - Square	(W) 12 (lm) 1112 / 1197 / 1224 (K) 3000K / 4000K / 6000K	15 1488 / 1601 / 1641 3000K / 4000K / 6000K	- -	- -
IP Rating	IP44			

Airflow by Duct Length

