Heat-Fan-Light Systems / Heat-Light Systems

These multi-function Heat-Fan-Light systems are designed to meet the higher operational demands of both small and large bathrooms. Fans incorporate a unique anti-condensate design and efficient LED centre lamps. All systems are supplied with duct, grille and wall switch. 5 year warranty.

The FAN2200 Heat-Light systems is designed to provide instant heat and additional lighting. A 150mm inline extraction fan kit, or Blue Jet fan and ducting combination, along with a 150-100mm reducer, can be added for a complete HEAT-FAN-LIGHT solution. 5 year warranty.

Heat-Fan-Light Systems									
Designer SATIN Low Profile	Duct (mm)	Fan Type	Total Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Heat Lamps	Fascia	Order Code
					(I/s)	(m³/hr)			
000	125	Centrifugal	1138	TBC	84	303	4 x 275W	White	FAN6882
3.6	120	Centinugai						Silver	FAN6883
@ @	125	Centrifugal	588	71	75	270	2 x 275W	White	FAN6880
00	120	Centinugai	300	71	75	210		Silver	FAN6881
Pro-Series	Duct (mm)	Fan Type	Total Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Heat Lamps	Fascia	Order Code
Low Profile					(I/s)	(m³/hr)			
00	125	Centrifugal	1180	83	60	216	4 x 275W	White	FAN0995
6000	125	Centrifugal	635	79	50	180	2 x 275W	White	FAN0940
Classic Standard Profile	Duct (mm)	Fan Type	Total Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Heat Lamps	Fascia	Order Code
					(l/s)	(m³/hr)			
000	100	Centrifugal	670	79	35	126	2 x 275W	White	FAN2162

Note: Installed system performance is always influenced by duct length and layout

Heat-Light Systems ¹⁾					
Classic Standard Profile	Duct (mm)	Total Watts (W)	Heat Lamps	Fascia	Order Code
86	100	650	2 x 275W	White	FAN2200

1) Note: Heat and light unit only - ready for the addition of an inline fan system (Order separately.

Accessories


Description	Chrome
275W Heat Lamp	LHT0081
LED Replacement Lamp for SATIN Units	LHT1107
LED Replacement Lamp for Pro-Series and Classic Units	LHT0211


Note: Free Air Fan Performances for FAN0995, FAN0940 and FAN2162 are actually installed system rates for 3 metres of duct, one 90 degree bend and one external grille.


Heat-Fan-Light Systems / Heat-Light Systems


Dimensions (mm)

Model	Cut-Out Size	A	В	C	D
FAN6882 FAN6883	320 x 320	370	125	210	370
FAN6880 FAN6881	375 x 202	419	125	198	244
FAN0995	300 x 300	338	125	170	338
FAN0940	390 x 220	435	125	185	260
FAN2162 FAN2200	390 x 220	450	100	195	250












Technical

Model	FAN6882 FAN6883	FAN6880 FAN6881	FAN0995	FAN0940	FAN2162	FAN2200		
Supply	220-240V AC, 50Hz							
Light	LED 4000K	LED 4000K	LED 3000K	LED 3000K	LED 3000K	LED 3000K		
Light Wattage	10W	10W	4.5W	4.5W	8W	8W		
Switch Plate	4-Way (supplied)	3-Way (supplied)	4-Way (supplied)	3-Way (supplied)	3-Way (supplied)	2-Way (supplied)		
Max. Operating Temp	40°C	40°C	40°C	40°C	40°C	40°C		
IP Rating	IPX4	IPX4	IPX4	IPX4	IPX4	IPX4		
Exterior Grille	125mm Fixed Louvre	125mm Fixed Louvre	125mm Eggcrate	125mm Eggcrate	100mm Eggcrate	-		
Duct	3m x 125mm	3m x 125mm	3m x 125mm	3m x 125mm	3m x 100mm	-		

Manrose Heat-Fan-Light systems have been tested to the downlight standard AS/NZS60598.2.2 Amendment A and are all classified as CA135.







www.simx.co.nz www.simx.co.nz