Through Wall Fan Kits - Quiet

MANROSE DESIGNER SERIES

QUIET

HEALTHY HOMES STANDARD PATHROOM

The new high-pressure and energy-efficient QUIET fan kits have ultra-high airflow without nuisance noise and are designed to be ducted straight through a bathroom or kitchen exterior wall. All kits include a weatherproof cowl. 5 year warranty.

Designer Standard Profile	Duct (mm)	Max. Fan Fan Type Watts		Max. Fan Pressure	Free Air Fan Performance		Specific Fan Power	Sound dB(A)	Switching	Order Code
	(11111)	турс	(W)	(Pa)	(l/s)	(m³/hr)	(W/I/s)	UD(A)		oouc
	150	Axial	22	138	114	410	0.19	41	Standard	FAN7190
									Timer	FAN7191
									Humidity Control	FAN7192
		125 Axial	15	68	54	194	0.28	38	Standard	FAN7187
	125								Timer	FAN7188
									Humidity Control	FAN7189

Note: Installed system performance is always influenced by duct length and layout


Switching Options

Standard Remote switch (not supplied).

- Timer Remote switch (not supplied). Fan continues operating for preset time after switching off. Timers are 2-30 minute adjustable and require permanent and switched phase.
- Humidity Remote switch (not supplied). The humidity control models come with an advanced inbuilt humidity automation controller.

Dimensions (mm)

Model	Cut-Out Size	A	В	C	D	E	F	G	H
FAN7190 FAN7191 FAN7192	168	174	30	150	375	146	111	30.5	227
FAN7187 FAN7188 FAN7189	140	160	30	125	375	120	100	29	185



Technical

Supply	220-240V AC, 50Hz			
Max. Operating Temp	40°C			
IP Rating	IPX4			
Exterior Grille	Weatherproof Cowl			
Duct	Aluminium Semi-Rigid			
Duct Length	375mm			



SENSING & CONTROL AUTOMATION

125mm BATHROOM FAN KITS

Quiet fan kits range now includes **NEW HUMIDITY MODELS**

Model	Standard Switching	Timer Switching	Humidity Control
125mm Through Wall Fan Kits	FAN7187	FAN7188	FAN7189
150mm Through Wall Fan Kits	FAN7190	FAN7191	FAN7192

www.simx.co.nz