

Duct Fittings

T-Branch Damper



Duct (mm)	Order Code
150	DCT1495
200	DCT1500

- Standard 240V drive open, drive close (D.O.D.C) motor attached
- Manufactured from ABS plastic
- Single damper motor and paddle control to direct airflow into or from selected branch
- Designed for both dual supply air and extract air applications
- Aesthetic smooth lines

Motorised Barrel Damper



Duct (mm)	Order Code
150	DCT1168
200	DCT1123
250	DCT1124
300	DCT1125
350	DCT1126
400	DCT1127

- Standard 240V drive open, drive close (D.O.D.C) motor attached
- Other voltages available upon request
- Manufactured from HDPE
- Braced for strength with 2 x 6mm steel rod rings
- 100% positive shut off and positive lock duct tabs
- Insulation meets AS1530 Part 3

Manual Barrel Damper



Duct (mm)	Order Code
150	DCT0787
200	DCT0706
250	DCT0788
300	DCT2706

- Manufactured from HDPE
- Complete with hand quadrant
- Braced for strength with 2 x 6mm steel rod rings
- Positive lock duct tabs
- Insulation meets AS1530 Part 3

Note: Nude combination fittings will be supplied in component form. We do NOT assemble.

Please enquire about any options not listed above that you may wish to order.