

Low Profile Flat Channel Ducting

Reducers



Description	Order Code
110 x 54 : 204 x 60	DCT0136
204 x 60 : 220 x 90	DCT1452
300 x 25 : 204 x 60	DCT1456

Designed to fit 204 x 60mm flat channel or airbrick

Elbow Bends

(with rotating offset spigot)



Duct (mm)	Dimensions W x H x D (mm)	Flow Rate Resistance (Pa)								Order Code	
		10 (l/s)	12 (l/s)	25 (l/s)	40 (l/s)	50 (l/s)	60 (l/s)	120 (l/s)	180 (l/s)		
100mm											
Ø 100 (M) : 110 x 54 (F)	115 x 90 x 140	5.6	8	33	74.5	101	137	-	-	DCT0124	
Ø 100 (F) : 110 x 54 (F)	115 x 90 x 140	5.6	8	33	74.5	101	137	-	-	DCT0015	
Ø 100 (M) : 204 x 60 (F)	215 x 80 x 195	2.9	7.1	28	68.1	92.2	118	-	-	DCT0521	
Ø 100 (M) : 220 x 90 (F)	226 x 118 x 240						5.3	20.4	44.8	-	DCT1444
Ø 100 (M) : 300 x 25 (F)										-	DCT2095
125mm											
Ø 125 (M) : 204 x 60 (F)	215 x 80 x 195	3.1	5.9	25	62.2	86	111	-	-	DCT0522	
Ø 125 (M) : 220 x 90 (F)	226 x 118 x 240						3.6	14.9	34.4	-	DCT1440
Ø 125 (M) : 300 x 25 (F)										-	DCT2096
150mm											
Ø 150 (M) : 204 x 60 (F)	215 x 80 x 195	2.8	4.9	21	41	53	67	-	-	DCT0523	
Ø 150 (M) : 220 x 90 (F)	226 x 118 x 240						9	34	75	-	DCT1441

Adjustable Bend - Horizontal



Duct (mm)	Order Code
204 x 60	DCT1480