

# Low Profile Flat Channel Ducting

## Airbrick Inserts



Description	Duct (mm)	Dimensions W x H x D (mm)	Flow Rate Resistance (Pa)						Order Code	
			10 (l/s)	12 (l/s)	25 (l/s)	40 (l/s)	50 (l/s)	60 (l/s)		120 (l/s)
Horizontal	204 x 60	210 x 65 x 85	3.2	7.8	20.9	96	128	176	-	DCT0137
Vertical	204 x 60	65 x 210 x 85	3.2	7.8	20.9	96	128	176	-	DCT1414

Horizontal: 110 x 54 duct connection requires reducer DCT0136

204 x 60 duct connection requires duct connector DCT0520

Vertical: Comes with duct connector DCT0520

## Double Airbrick



Duct (mm)	Dimensions W x H x D (mm)	Flow Rate Resistance (Pa)			Order Code
		60 (l/s)	120 (l/s)	180 (l/s)	
220 x 90	245 x 145 x 80	37.4	74.8	112.2	DCT1450

## Double Airbrick Adapter



Duct (mm)	Dimensions W x H x D (mm)	Flow Rate Resistance (Pa)			Order Code
		60 (l/s)	120 (l/s)	180 (l/s)	
220 x 90	226 x 132 x 52	10.4	37	81.5	DCT1451

## Double Airbrick Adapter to Round Duct



Duct (mm)	Dimensions W x H x D (mm)	Order Code
100/125/150	235 x 140	DCT1453