

Rapid Dry


An internal UV-C chamber sterilises the air before contact is made with hands. Intelligent control only switches the heat element on when ambient temperature is <25°C, saving energy when not needed. The robust stainless steel casing provides protection in higher risk areas. Auto shut off after 45sec to prevent overheating or continuous running. 2 year warranty.



Fan Input (W)	Heater Input (W)	Air Speed (km/hr)	Dry Time (sec)	Housing	Colour	Order Code
500	650	216	10-15 (approx)	1.2mm Stainless Steel 304	Brushed Stainless	FAN6855

Dimensions (mm)

Model	A	B	C	Net Weight (kg)
FAN6855	172	253	145	3.0



General Information

Supply	220-240V AC
Filter	Coarse Particulate Filter
UV-C Sterilisation	Yes
Auto Shut Off (sec)	45
Intelligent Auto Heat Off	≥ 25°C
Manual Switch Heat Off	Yes
Sound Level @ 1m	72 dB(A)
Safety	Class I
IP Rating	IPX1
IK Rating	IK08

Recommended Mounting Heights for All Compact Wall Dryers (to bottom of the unit)

Men's Washrooms	1000mm
Women's Washrooms	960mm
Disabled Washrooms	860mm
Children's Washrooms	
10-13 years	910mm
7-10 years	860mm
4-7 years	812mm