

DATA SHEET

ALVA BL 540/170 TR 180° 600 830 AN

Item number EL10820687
GTIN 4015120820687



230 V ~	16 W		IP65		IK10	
LED 3000 K	CRI >80	ON/OFF				

Product description

- LED bollard made from high-grade aluminium
- Dirt-repellent thanks to powder coating with lotus effect
- Integrated ballast , installation without further accessories
- High-quality housing, die-cast aluminium, charcoal grey powder-coated, similar to RAL 7024
- Colour temperature 3000 K

Offers special product features like:

- Protected against sea air



Technical data

GENERAL	
Device category	Bollard light
Remote controllable	–
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years

ATTACHMENT	
Installation type	Free standing
Installation position	Floor
Type of connection	Push terminal
Connectable wire cross section	1,50 – 2,50 mm ²
Number of contacts	3

HOUSING	
Dimensions	Height/Depth 540 mm, Ø 170 mm
Weight	8925 g
Material	powder-coated aluminium
Protection type	IP65
Permissible ambient temperature	-25 °C...+40 °C
Relative humidity	5 - 95 %, non-condensing
Impact resistance	IK10
Colour	graphite gray, similar to RAL 7024

ELECTRICAL VERSION	
Control system	ON/OFF
Protection class	I

Nominal voltage	110 - 240 V AC / 50 - 60 Hz
In-rush current	13 A / 57 µs
Leakage current	0,31 mA
Power consumption	65 mA

LIGHT	
Diffusor	transparent
Light emission	direct
Beam angle	159 °
Flicker factor	<3 %
Rated output P	16 W
Luminous Flux (light)	760 lm
Luminous efficacy	47,00 lm/W
Colour temperature	3000 K
Colour rendering index Ra	> 80
Colour tolerance	SDCM < 3
Color Quality Scale	80
L70B10 lifetime at 25 °C	105000 h
Life time L70B50 at 25 °C	110000 h
Life time L80B10 at 25 °C	65000 h
Life time L80B50 at 25 °C	70000 h
Life time L90B10 at 25 °C	35000 h
Life time L90B50 at 25 °C	35000 h
Photobiological safety	RG0
Energy efficiency class	A++ to A

DATA SHEET


ALVA BL 540/170 TR 180° 600 830 AN

Item number **GTIN**
EL10820687 4015120820687

Accessories

Product designation	GTIN
Mounting	
ALVA GROUND ANCHOR	4015120820083

Scale drawing



Light distribution

