

## ALVA BL 700/100 TR 360° 600 840 WH

**Item number** EL10821141  
**GTIN** 4015120821141



### Product description

- LED bollard made from high-grade aluminium
- Dirt-repellent thanks to powder coating with lotus effect
- Integrated ballast (on/off), installation without further accessories
- High-quality housing, die-cast aluminium, powder coated white, similar to RAL 9016
- Colour temperature 4000 K

### Offers special product features like:

- Protected against sea air

### Technical data

GENERAL	
Device category	Bollard light
Remote controllable	–
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years
ATTACHMENT	
Installation type	Free standing
Installation position	Floor
Type of connection	Push terminal
Connectable wire cross section	1,50 – 2,50 mm <sup>2</sup>
Number of contacts	5
HOUSING	
Dimensions	Height/Depth 700 mm, Ø 100 mm
Weight	3250 g
Material	powder-coated aluminium
Protection type	IP65
Permissible ambient temperature	-25 °C...+40 °C
Relative humidity	5 - 95 %, non-condensing
Colour	white, similar to RAL 9016
ELECTRICAL VERSION	
Control system	ON/OFF


Protection class	I
Nominal voltage	110 - 240 V AC / 50 - 60 Hz
In-rush current	13 A / 57 µs
Leakage current	0,31 mA
LIGHT	
Diffusor	transparent
Light emission	direct
Beam angle	160 °
Flicker factor	< 3%
Rated output P	7 W
Luminous Flux (light)	560 lm
Luminous efficacy	80,00 lm/W
Colour temperature	4000 K
Colour rendering index Ra	> 80
Color Quality Scale	>80
L70B10 lifetime at 25°C	105000 h
Life time L70B50 at 25 °C	110000 h
Life time L80B10 at 25 °C	65000 h
Life time L80B50 at 25 °C	70000 h
Life time L90B10 at 25 °C	35000 h
Life time L90B50 at 25 °C	35000 h
Photobiological safety	RG0
Energy efficiency class	A++ to A

# DATA SHEET

## ALVA BL 700/100 TR 360° 600 840 WH

**Item number**      **GTIN**  
EL10821141      4015120821141

### Scale drawing



### Light distribution

