

DATA SHEET

House number ALVA WL 15W 4000K WH MILKY AUTO

Item number EL10840234
GTIN 4015120840234



230 V ~			IP 65		IK09	LED 4000 K
CRI >80	r 8 m	140°	ON/OFF			

Product description

- High-quality aluminium LED automatic house number light
- Dirt-repellent thanks to powder coating with lotus effect
- Motion detectors and switch input for switching operating states

Offers special product features like:

- Integrated motion detector
- Protected against sea air

Technical data

GENERAL

Device category	Wall light
User interface	IR remote control, Push button input
Remote controllable	✓
Conformity	CE, EAC, RoHS, WEEE

ATTACHMENT

Installation type	Surface mounting
Installation position	Ceiling / wall
Type of connection	Push terminal
Connectable wire cross section	1,50 - 2,50 mm ²
Number of contacts	4

HOUSING

Dimensions	Length 250 mm x Width 200 mm x Height/ Depth 75 mm
Weight	1684 g
Material	powder-coated aluminium
Protection type	IP65
Permissible ambient temperature	-25 °C...+40 °C
Impact resistance	IK09
Colour	white, similar to RAL 9016
Glow wire test in accordance with IEC 60695-2-10	650 °C

ELECTRICAL VERSION

Control system	ON/OFF
Protection class	I
Nominal voltage	230 V / 50 Hz
In-rush current	6 A / 520 µs
Leakage current	0,016 mA
Power consumption	90 mA

LIGHT

Diffusor	opal
Light emission	direct
Beam angle	120 °
Flicker factor	<10 %
Rated output P [W]	15 W
Luminous flux [lm]	1005 lm
Luminous efficacy	67 lm/W
Colour temperature	4000 K
Colour rendering index Ra	> 80
Colour tolerance	SDCM < 3
Color Quality Scale	80

SENSORS


Detection angle	140°
Recommended installation height	3 m
Max. mounting height	5 m

DATA SHEET


House number ALVA WL 15W 4000K WH MILKY AUTO

Item number **GTIN**
EL10840234 4015120840234

Dimension drawing



Field of detections



Detection range

Light distribution

