

ISABELLE PDL 1200 DDP TR 8800 840 DALI BK

Item number E010306174
GTIN 4015120306174



Product description

- LED pendant light, LED output 72 W, for workplace-oriented lighting in offices and meeting rooms with glare-free direct component and indirect light
- Sleek, timeless design
- Ballast (DALI) integrated
- High-quality housing, aluminium lamp bodies, anthracite powder coated
- Colour temperature 4000 K
- Excellent light quality, no flickering



Technical data

GENERAL	
Device category	Pendant light
User interface	DALI-Bus
Remote controllable	–
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years
ATTACHMENT	
Installation type	Pendant
Installation position	Ceiling
HOUSING	
Dimensions	Length 1206 mm x Width 166 mm x Height/Depth 30 mm
Weight	5920 g
Material	Aluminium
Surface finish	Powder-coated
Protection type	IP20
Permissible ambient temperature	0 °C...+40 °C
Relative humidity	5 - 93 %, non-condensing
Colour	black, similar to RAL 9004
Glow wire test in accordance with IEC 60695-2-10	650 °C
ELECTRICAL VERSION	
Control system	DALI
Protection class	I

Nominal voltage	220 - 240 V AC / 50 - 60 Hz
Stand-by consumption	< 1 W
LIGHT	
Diffusor	transparent
Glare suppression	DDP (micro-prismatic)
Light emission	direct/indirect
Beam angle	80 °
Unified Glare Rating	≤ 19
Flicker factor	< 3 %
Rated output P	78 W
Luminous Flux (light)	8830 lm
Luminous efficacy	113,00 lm/W
Colour temperature	4000 K
Colour rendering index Ra	> 80
Colour tolerance	SDCM < 3
Color Quality Scale	CQS > 80
L70B10 lifetime at 25 °C	70000 h
Life time L70B50 at 25 °C	80000 h
Life time L80B10 at 25 °C	45000 h
Life time L80B50 at 25 °C	50000 h
Life time L90B10 at 25 °C	25000 h
Life time L90B50 at 25 °C	25000 h
Photobiological safety	RG1
Energy efficiency class	A++ to A


ISABELLE PDL 1200 DDP TR 8800 840 DALI BK

Item number **GTIN**
E010306174 4015120306174

Accessories

Product designation	GTIN
Adapter	
ISABELLE PDL CONNECTING PLATE BK	4015120306259

Scale drawing



Light distribution