

ISABELLE PDL 1200 DDP TR 8800 840 PD IR DALI WH

Item number E010306204
GTIN 4015120306204



Product description

- LED pendant light, LED output 72 W, for workplace-oriented lighting in offices and meeting rooms with glare-free direct component and indirect light
- Sleek, timeless design
- Ballast (DALI) integrated
- Presence control, override using push button and remote control
- High-quality housing, aluminium lamp bodies, powder-coated white
- Colour temperature 4000 K
- Excellent light quality, no flickering

Offers special product features like:

- Integrated presence detector with DALI bus voltage supply
- Simple parameterisation, remote control and documentation with ESY-Pen and ESY-App



Technical data

GENERAL

Device category	Pendant light
User interface	IR remote control, DALI-Bus
Remote controllable	✓
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years

ATTACHMENT

Installation type	Pendant
Installation position	Ceiling

HOUSING

Dimensions	Length 1206 mm x Width 166 mm x Height/Depth 30 mm
Weight	6040 g
Material	Aluminium
Surface finish	Powder-coated
Protection type	IP20
Permissible ambient temperature	0 °C...+40 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9003
Glow wire test in accordance with IEC 60695-2-10	650 °C

ELECTRICAL VERSION

Control system	DALI
Protection class	I
Nominal voltage	220 - 240 V AC / 50 - 60 Hz
Stand-by consumption	1.0 W

LIGHT

Diffusor	transparent
Glare suppression	DDP (micro-prismatic)
Light emission	direct/indirect
Beam angle	80 °
Unified Glare Rating	≤ 19
Flicker factor	< 3 %
Rated output P	80 W
Luminous Flux (light)	8830 lm
Luminous efficacy	110,00 lm/W
Colour temperature	4000 K
Colour rendering index Ra	> 80
Colour tolerance	SDCM < 3
Color Quality Scale	CQS > 80
L70B10 lifetime at 25 °C	70000 h
Life time L70B50 at 25 °C	80000 h
Life time L80B10 at 25 °C	45000 h
Life time L80B50 at 25 °C	50000 h
Life time L90B10 at 25 °C	25000 h
Life time L90B50 at 25 °C	25000 h
Photobiological safety	RG1
Energy efficiency class	A++ to A

SENSORS

Detection angle	360°
Detection range diagonally	Ø 3 m
Detection range head-on	Ø 3 m
Detection range presence	Ø 2 m
Field of detection	7 m ²

ISABELLE PDL 1200 DDP TR 8800 840 PD IR DALI WH


Item number	GTIN
E010306204	4015120306204

Light measurement mixed light


Accessories

Product designation	GTIN
Adapter	
ISABELLE PDL CONNECTING PLATE WH	4015120306242
Remote control	
ESY-Pen	4015120425356
ISABELLE REMOTE CONTROL	4015120306082

Scale drawing



Field of detections



Detection range

Diagonally (A)	∅ 3 m
Frontal (B)	∅ 3 m
Presence area (C)	∅ 2 m

Light distribution