DATA SHEET

ESYLUX

PD-C 360i/24 DUOplus-SM

Item number	GTIN
EP10426810	4015120426810



5 YEARS MANUFACTURER WARRANTY

Ø 24 m | 360° | ON/OFF | IP20 | 2 CH | 1 CH | IR

Product description

- Presence detector with **360° field of detection** for ceiling mounting **Surface mounted (plaster)**
- **range of up to 24 m** in diameter at a recommended installation height of 3 m and for the **independent control of 2 lighting areas** (window and internal areas) depending on presence and natural light
- Additional HVAC switch contact (channel 3) for switching an additional light source or controlling heating, ventilation and air conditioning depending on presence
- Both light channels and the HVAC contact with 16 A high-performance relay (tungsten pre-contact)
- Default settings ensure immediate operability

Special Product Features:

- Simple parameterisation, remote control and documentation with ESY-Pen and ESY-App

Technical data

GENERAL	
Device category	Ceiling-mounted presence detector
Product information	Please note the Explanation of circuit breaker in the download area of the product!
User interface	Adjusting controller, IR remote control
Remote controllable	✓
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years

ATTACHMENT	
Installation type	Surface mounted (plaster)
Installation position	Ceiling
Type of connection	Push terminal
Connectable wire cross section	1.5 mm²

HOUSING	
Dimensions	Height 74 mm, Ø 108 mm
Weight	221 g
Material	UV-stabilised polycarbonate
Protection type	IP20
Permissible ambient temperature	-25 °C...+50 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9010

ELECTRICAL VERSION	
Control system	ON/OFF
Protection class	II
Nominal voltage	230 V ~ / 50 Hz
In-rush current	800 A / 200 µs
Power consumption	0.3 W

SENSORS	
Detection angle	360°
Detection range tangential Manual measurement	Ø 24 m
Detection range tangential Automated measurement in accordance with IEC 63180/AMD1 / sensNORM 3.0	Ø 24 m
Detection range radial Automated measurement in accordance with IEC 63180/AMD1 / sensNORM 3.0	Ø 8 m
Detection range presence Automated measurement in accordance with IEC 63180/AMD1 / sensNORM 3.0	Ø 6 m
Field of detection	up to 453 m²
Recommended installation height	3 m
Max. mounting height	10 m
Light measurement	mixed light
Level of brightness	5 - 2000 lx

CHANNELS (LIGHTING / HVAC)	
Number of light channels	2
Number of HVAC-channels	1
Push button input lighting	2
Push button input HVAC	✓
Slave input	✓
Max. number of slave detectors	10
Mode	Semi-automatic, Fully automatic
Switching delay from "dark to light"	300 s
Switching delay from "light to dark"	30 s

DATA SHEET

PD-C 360i/24 DUOplus-SM

Item number	GTIN
EP10426810	4015120426810

Constant light control	-
Channel	**C1** Lighting
Function	Switching
Switching capacity	230 V/50 Hz 2300 W/10 A (cos phi = 1) 1150 VA/5 A (cos phi = 0,5) 600 W LED
Switch contact	make contact / non-floating
Push button input	✓
Impulse mode	✓
Switch-off delay time	60 s...30 min (adjustable in steps)
Channel	**C2** Lighting
Function	Switching
Switching capacity	230 V/50 Hz 2300 W/10 A (cos phi = 1) 1150 VA/5 A (cos phi = 0,5) 600 W LED
Switch contact	make contact / non-floating
Push button input	✓
Impulse mode	✓
Switch-off delay time	60 s...30 min (adjustable in steps)
Channel	**C3** HVAC
Function	Switching
Switching capacity	230 V/50 Hz, 16 AX 1000 W/4,5 A (cos phi = 1) 500 VA/2,25 A (cos phi = 0,5) 250 W LED
Switch contact	make contact / floating
Push button input	-
Impulse mode	-
Switch-off delay time	60 s...15 min (adjustable in steps)

Factory settings

GENERAL	
Sensitivity	100 %

CHANNELS (LIGHTING / HVAC)	
Channel	**C1** Lighting
Operating mode	fully automatic
Level of brightness/switching threshold	400 lx
Switch-off delay time	5 min
Duration of switch-off warning	300 s
Channel	**C2** HVAC
Operating mode	fully automatic
Level of brightness/switching threshold	400 lx
Switch-off delay time	30 min
Duration of switch-off warning	300 s

Accessories

Product designation	Item number	Product description	GTIN
Ceiling-mounted presence detector			
PD-C 360/8 Slave	EP10055379	Slave presence detector for extending the field of detection of a Master presence detector	4015120055379
PD-C 360/24 Slave	EP10055386	Slave presence detector for extending the field of detection of a Master presence detector	4015120055386
PD-C 360/32 Slave	EP10427770	Slave presence detector for extending the field of detection of a Master presence detector	4015120427770
Electrical accessories			
FILTER 230 V	EP10426988	Filter for suppression of inductive loads, such as relays, contactors, fluorescent lamps and transformers	4015120426988
Protection			
BASKET GUARD ROUND LARGE	EM10425608	Basket guard for presence and motion detectors and smoke detectors, Ø 180 mm, height 90 mm	4015120425608
Remote control			
ESY-Pen	EP10425356	ESY-Pen and ESY-App, two tools for every task: (1) Parameterisation, (2) remote control, (3) light measurement, (4) project management	4015120425356
REMOTE CONTROL PDi/plus	EM10425530	IR remote control for multi-channel presence detectors of the COMPACT series (DIM, DUOplus, DUO DIM, DUO DIMplus)	4015120425530
REMOTE CONTROL PDi/USER	EM10425547	IR remote control for end users of presence detectors	4015120425547

DATA SHEET

PD-C 360i/24 DUOplus-SM

Item number	GTIN
EP10426810	4015120426810

Field of detections



Detection range

Installation height	Tangential A Manual measurement	Tangential A Automated measurement in accordance with IEC 63180/AMD1 / sensNORM 3.0	Radial B Automated measurement in accordance with IEC 63180/AMD1 / sensNORM 3.0	Presence C Automated measurement in accordance with IEC 63180/AMD1 / sensNORM 3.0
2.5 m		Ø 24 m	Ø 6 m	Ø 6 m
3 m	Ø 24 m	Ø 24 m	Ø 8 m	Ø 6 m
5 m		Ø 25 m	Ø 9 m	
10 m		Ø 28 m	Ø 11 m	

Dimension drawing



Circuit diagram



Standard operation with optional control via a closing button and use of max. ten slave devices to one master device.

DATA SHEET

PD-C 360i/24 DUOplus-SM

Item number	GTIN
EP10426810	4015120426810

Detailed product description

- Presence detector with **360° field of detection** for ceiling mounting **Surface mounted (plaster)**
- **range of up to 24 m** in diameter at a recommended installation height of 3 m and for the **independent control of 2 lighting areas** (window and internal areas) depending on presence and natural light
- Additional HVAC switch contact (channel 3) for switching an additional light source or controlling heating, ventilation and air conditioning depending on presence
- Both a light channel and an HVAC contact with 16 A high-performance relay (tungsten pre-contact), ideal for switching capacitive loads such as electronic ballasts, parallel-compensated fluorescent lamps, compact fluorescent lamps, energy saving lamps
- Ideal for use in **installations in large heights of up to 10 m**, such as sports halls, warehouses etc.
- Default settings ensure immediate operability
- Simple programming using remote control with "blue mode" technology or setting elements
- Integrated toggle for setting with remote control or by adjusting controller - prevents operating errors and provides tamper protection
- Masking of interference sources by reducing sensitivity using DIP switches
- Additional switch input per channel with toggle function "room = ON + OFF/hallway = ON"
- Detector can be used as a fully automatic or semi-automatic device
- Surface-mounted device as standard
- Field of detection can be extended by connecting slave devices
- Targeted masking out of areas by means of an enclosed lens mask