


DATA SHEET

CELINE PNL 1200 LDP SO 3600 840 IP20 DALI

Item number EQ10126055
GTIN 4015120126055



Technical data

GENERAL	
Device category	Recessed light
User interface	DALI-Bus
Remote controllable	–
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years
ATTACHMENT	
Installation type	Insert
Installation position	Ceiling
Installation dimension	Installation length: 1200 mm x Installation width: 300 mm x Installation depth: 140 mm
HOUSING	
Dimensions	Length 1195 mm x Width 296 mm x Height/Depth 91 mm
Weight	4805 g
Material	Varnished steel
Surface finish	frosted
Protection type	IP20
Permissible ambient temperature	0 °C...+40 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9003
Glow wire test in accordance with IEC 60695-2-10	650 °C
ELECTRICAL VERSION	

Product description

- LED light with opal (MILKY) cover (diffuser)
- Can be used as a panel light for ceiling systems with concealed or visible mounting rails for system dimensions 1200 x 300 mm (please note any special features and restrictions of the ceiling system manufacturer)
- LED output 30 W
- Integrated ballast (DALI), installation without further accessories
- Colour temperature approx. 4000 K (neutral white)

Control system	DALI
Protection class	II
Nominal voltage	230 V AC / 50 Hz
LIGHT	
Diffusor	semi-opal
Glare suppression	LDP (linear-prismatic)
Light emission	direct
Beam angle	90 °
Unified Glare Rating	≤ 19
Flicker factor	< 3 %
Rated output P	33 W
Luminous Flux (light)	3590 lm
Luminous efficacy	108,00 lm/W
Colour temperature	4000 K
Colour rendering index Ra	> 80
Colour tolerance	SDCM < 3
Color Quality Scale	> 80
L70B10 lifetime at 25 °C	75000 h
Life time L70B50 at 25 °C	95000 h
Life time L80B10 at 25 °C	50000 h
Life time L80B50 at 25 °C	60000 h
Life time L90B10 at 25 °C	25000 h
Life time L90B50 at 25 °C	30000 h
Photobiological safety	RG0
Energy efficiency class	A++ to A

DATA SHEET


CELINE PNL 1200 LDP SO 3600 840 IP20 DALI

Item number **GTIN**
EQ10126055 4015120126055

Accessories

Product designation	GTIN
Mounting	
MOUNTING FRAME 1200/1250 SM WH	4015120113765
Protection	
DROP PROTECTION	4015120121616

Scale drawing



Light distribution

