Simx

CHIMES

PORTABLE / PLUG-IN WIRED / WIRELESS ENTRY ALERTS / ALARMS

CHIMES

Simx

Diversity of Style

Simx chimes offer a comprehensive range of styles, tones and connections to suit any entrance decor or application.

Portable Wireless Chimes

Plug-in Wireless Chimes

Wired Chimes

Entry Alerts

Versatility of application

The range provides options for both traditional and modern decor with wired, wireless and plug-in installation options available.

PORTABLE CHIMES - WIRELESS

Decor

Chime and Door Press Kit

Features

- Compact and modern style
- Select tune, strobe, or tune and strobe output
- Auto learning code to avoid interference conflicts
- Duplicate kits can be paired to provide multiple door presses or chimes
- 1 year warranty

Technical Specifications*

Tunes		36
Max. Operating Range		Up to 80m
Sound Level @1m		Up to 75 dB(A)
Volume Levels		3
Mounting	Chime	Wall or table (base supplied)
	Door Press	Wall
Batteries	Chime	2 x AA (not included)
	Door Press	1 x CR2032 (included)
IP Rating	Door Press	IP44

Range

Product	Code
Chime and Door Press Kit - Black/Silver	CHM0157
Chime and Door Press Kit - White/Silver	CHM0158

SmartChime

Chime and Door Press Kit

Features

- Complete with belt clip for portable use or wall mount
- Flashing indicator LED light for the hearing impaired
- Auto learning code to avoid interference conflicts
- 1 year warranty

Technical Specifications*

Tunes		36
Max. Operating Range		Up to 80m
Sound Level @1m		60 - 85 dB(A) (adjustable)
Volume Levels		4
Mounting	Chime	Wall or table (base supplied)
	Door Press	Wall
Batteries	Chime	2 x AA (not included)
	Door Press	12V/23A (included)
IP Rating	Door Press	IP44

Range

Product	Code
Chime and Door Press Kit - White	CHM0155

* *Operating radio frequency is 433 - 92 MHz*
Operating range and sound levels are measured in free field conditions

Operating temperature range for chimes is 0°C to 30°C
Operating temperature range for door presses is -10°C to 50°C

PLUG-IN CHIMES - WIRELESS

Kinetic

Chime and Door Press Kit

Features

- No battery required door press
- Up to 30 kits can be paired for multiple entrances or large houses
- Flashing light designed for hearing impaired
- 1 year warranty

Technical Specifications*

Tunes		58
Max. Operating Range		Up to100m
Sound Level @1m		25 - 85 dB(A)
Volume Levels		5
Mounting	Chime	Plug-in
	Door Press	Wall
Batteries	Door Press	Not required
IP Rating	Door Press	IP44

Range

Product	Code
Chime and Door Press Kit - White	CHM0181

VisiChime

Chime and Door Press Kit

Features

- Contemporary style, for use throughout the home
- Able to add an extra door press for the back door
- Flashing strobe light for the hearing impaired
- User adjustable coding system ensures no interference from neighbours chimes
- 1 year warranty

Technical Specifications*

Tunes		1
Max. Operating Range		Up to 35m
Sound Level @1m		74 dB(A)
Volume Levels		3
Mounting	Chime	Plug-in
	Door Press	Wall
Batteries	Door Press	12V/23A (included)
IP Rating	Door Press	IP65

Range

Product	Code
Chime and Door Press Kit - White	CHM0100
Additional Door Press	CHM0099

* *Operating radio frequency is 433 - 92 MHz*
Operating range and sound levels are measured in free field conditions

Operating temperature range for chimes is 0°C to 30°C
Operating temperature range for door presses is -10°C to 50°C

Sunrise and Sunset

Chime and Door Press Kit

Features

- Simple pairing to eliminate neighbour conflict
- Flashing light designed for hearing impaired
- Up to 30 chimes can be paired to a single door press
- Up to 30 door presses can be paired to a single chime unit, with same, or mix, of different tones
- 1 year warranty

Technical Specifications*

Tunes		52
Max. Operating Range		Up to 100m
Sound Level @1m		25 - 85 dB(A)
Volume Levels		4
Mounting	Chime	Plug-in
	Door Press	Wall
Batteries	Door Press	1 x CR2032 (included)
IP Rating	Door Press	IP55

Range

Product	Code
Sunrise Chime and Door Press Kit - Black	CHM0165
Sunrise Chime and Door Press Kit - White	CHM0166
Sunset Chime and Door Press Kit - White	CHM0167
Additional Door Press - Black	CHM0168
Additional Door Press - White	CHM0169

* *Operating radio frequency is 433 - 92 MHz*
Operating range and sound levels are measured in free field conditions

Operating temperature range for chimes is 0°C to 30°C
Operating temperature range for door presses is -10°C to 50°C

CHIMES - WIRED

Built-In Transformer

Mechanical Chime and Door Press

MIRA

LEDA

Features

- Door press required (order separately)
- Integral transformer for convenient installation
- 1 year warranty

Technical Specifications*

Tones		Ding Dong
Sound Level @1m		>80 dB(A)
Voltage	Chime	230V AC
Mounting	Chime	Wall
	Door Press	Wall
IP Rating	All Items	IP20
Dimensions		170mm (H) x 110mm (W)

Range

Product	Code
Mira Chime - White	CHM0173
Leda Chime - White	CHM0174

Door Presses

Product	Code
Cosmos Unlit Door Press - White	CHM0177
Cosmos Unlit Door Press - Black	CHM0178
Quasar Lit Door Press - White	CHM0179
Quasar Lit Door Press - Black	CHM0180

Note: Lit door presses require the use of a transformer, do not use with battery powered chimes as batteries will discharge rapidly.

Remote Transformer

Mechanical Chime and Door Press

JUNO

INDI

Features

- Door press required (order separately)
- Remote transformer required (order separately)
- 1 year warranty

Technical Specifications*

Tones		Ding Dong
Sound Level @1m		>75 dB(A)
Voltage	Chime	8V AC (from transformer)
Batteries	Chime	1 x 9V (not included)
Mounting	Chime	Wall
	Door Press	Wall
	Transformer	DIN Rail/Surface
IP Rating	All Items	IP20
Dimensions		120mm (H) x 120mm (W)

Range

Product	Code
Juno Chime - White	CHM0175
Indi Chime - White	CHM0176

Transformers

Product	Code
Transformer - 8V 2A	CHM0024
Transformer - 8V 1A	CHM0172
Transformer - 8V 1A	CHM0182

* *Operating range and sound levels are measured in free field conditions*

Operating temperature range for chimes is 0°C to 30°C
Operating temperature range for door presses is -10°C to 50°C

PIR Alarm

Alarm and Remote Sensor Kit

Features

- Remote sensor activation on presence detection
- Perfect for long driveways
- Flashing LED's and loud alarm
- 'Ding Dong' alert sound
- Hi - low volume selection
- 1 year warranty

Technical Specifications*

Tunes		1
Max. Operating Range		Up to 120m
PIR Sensing Angle		80° x 8m (approx)
Sound Level @1m		Up to 90 dB(A)
Mounting	Chime	Wall
	Sensor	Wall
Batteries	Door Press	3 x C (not included)
	Sensor	3 x AAA 1,5V (not included)
IP Rating	Sensor	IP44

Range

Product	Code
Alarm and Sensor Kit - White	CHM0152

Password PIR Siren

Siren and Sensor

Features

- Activation on presence detection, until 4 digit password is entered
- Excellent DIY security for no-go zones
- 'Ding Dong' or siren alert sound
- 1 year warranty

Technical Specifications*

Tunes	2
Max. Operating Range	Up to 120m
PIR Sensing Angle	120° x 5m (approx)
Sound Level @1m	Up to 85 dB(A)
Mounting	Wall (adjustable)
Batteries	3 x AAA 1,5V (not included)
IP Rating	IP44
Password Code	256 combinations

Range

Product	Code
Siren and Sensor - White	CHM0156

* *Operating radio frequency is 433 - 92 MHz*
Operating range and sound levels are measured in free field conditions

Operating temperature range for chimes is 0°C to 30°C
Operating temperature range for door presses is -10°C to 50°C

Distributed by Simx Limited, PO Box 14347, Panmure, Auckland 1741, New Zealand
p +9 259 1660 | **e** enquiry@simx.co.nz | **w** www.simx.co.nz

PUB1537 2112