





BI-SYMMETRIC MODELS
ASYMMETRIC MODELS

15W



3K/4K

LED

COLOURS









## BARON LED BOLLARD

BARON is an ideal bollard for entryways, pathways and most pedestrian-scale applications that require unique aesthetics and superior performance.



1000mm Bollard Standard

#### **Unique Curved Design**

No screws exposed, polished and elegant fixture body. Not only does this reveal the beauty of art of light, but also makes full use of the lumen output because no front projection light will be blocked.


This exquisite design, together with the robust IK10 die-cast alloy body and versatile 'no upward light' optical systems, BARON looks like a reliable guardian standing on the ground, driving away the darkness, and bringing light and safety to your pathway.

Widely used for pathway lighting, landscape enhancement, security purposes, commercial spaces, public areas, car parks, and waterfront locations.

#### **TECHNICAL SPECIFICATIONS**

220-240V AC 50Hz **Power Source** CRI >80 **IP Rating** IP66 Wattage 15 Watts, 0.07A (running) **IK Rating** IK10 Luminous Flux 1500 lm (Bi-Symmetric) 1450 lm (Asymmetric) Safety Class I **LED Colour** 3000K or 4000K Mounting **Ground Mount PIR Detection Angle** Max 120deg Operating Temperature -20°C to + 40°C **PIR Detection Range** Max 3 mtrs radius **Net Weight** 4.8 Kg Warranty 5 years PIR Time ON 5 sec - 8 min adjustable

#### **DIMENSIONS**










### **DISTRIBUTION CURVE**

Baron Bi-Symmetric Optics



**Baron Asymmetric Optics** 







# BARON LED BOLLARD

#### **PRODUCT CODES**

**Bi-Symmetric Models** 

LHT1199 - Standard 3K

LHT1200 - Standard 4K

LHT1201 - with PIR Sensor 3K

LHT1202 - with PIR Sensor 4K

Asymmetric Models

LHT1211 - Standard 3K

LHT1212 - Standard 4K

LHT1213 - with PIR Sensor 3K

LHT1214 - with PIR Sensor 4K

Accessory

LHT1203 - Baron Inground 500mm Anchor



