



# Product Catalogue

CEILING SWEEP FANS



## Ceiling Sweep Fans

## **Ceiling Sweep Fans**

## **Table of Contents**

## **Ceiling Sweep Fans**

Ceiling Fan Selector Guide	202
Skyfan DC 3 Blade Skyfan DC 3 Blade with LED	204 204
Spyda 4 Blade Spyda 4 Blade with LED	205 205
Spyda 3 Blade Spyda 3 Blade with LED	206 207
Spinika 4 Blade Spinika 4 Blade with LED	208 208
Stanza 3 Blade Stanza 3 Blade with Light	209 209
Royale II DC 4 Blade	210
Seattle DC 3 Blade	210
Mariah 5 Blade with LED	211
Malibu IP55 4 Blade	211
National 4 Blade	211
Cooling Fans	
Zephyr II Wall Mount Fans	212
Orbital Ceiling Mount Fans	213
Wall Fans	214

www.simx.co.nz 201

# CEILING FAN SELECTOR GUIDE

#### Saving money, and the environment

Ceiling fans create a substantial cooling affect by gently circulating the air at a fraction of the cost of air conditioning.

## SMALL ROOMS

**(900mm) 36"** - ideal for small bedrooms or any application that has limited space.



## MEDIUM ROOMS & OUTDOOR AREAS

(1220mm) 48" and (1250mm) 50" - ideal for small to medium sized rooms such as bedrooms or smaller living areas.





## LARGE BEDROOMS, LIVING ROOMS & OUTDOOR AREAS

(1300mm) 52" and (1400mm) 56" - ideal for large bedrooms or master bedrooms and living areas.



## LARGE LIVING AREAS & OUTDOOR AREAS


(1500mm) 60" and (1570mm) 62" - ideal for large open space living areas and large outdoor alfresco areas.



## **CEILING HEIGHT**

Ventair fans are designed to suit ceiling heights of 2.45m - 3.05m. (ie, blade clearance of 2.1m - 2.7m from floor).

A range of extension rods and joiner kits are available for ceiling heights above 3.05m.





## **Ceiling Sweep Fans**



Skyfan DC ceiling fans are intelligent energy saving DC technology using up to 75% less power consumption. Lightweight glass fibre composite blades for added strength and durability as well as an inbuilt anti-vibration system. Reversible function is available on the 6-speed LCD remote controller with ECO, sleep and timer functions. Ceiling fans are 220-240V AC, 50Hz operated and come complete with ECO airflow function. Suitable for indoor and covered outdoor areas. 5 year warranty.

Skyfan DC 3 BLADE	Sweep Dia. (mm)	Fan Speed (RPM) 1, 2, 3, 4, 5, *ECO	Max Air Delivery (m³/min)	Wattage L-H (W)	Colour	Order Code	
	900	100/150/190/220/270/*120	208	3-32	White	SKY903WH	
	900	100/130/190/220/270/ 120	200	3-32	Black	SKY903BL	
	1200	05 /4 40 /4 70 /000 /000 /*44 5	232	0.0.01	0.001	White	SKY1203WH
	1200	95/140/170/200/230/*115	0/200/230/*115 232 3.6-31	3.0-31	Black	SKY1203BL	
		90/132/166/190/210/*110	244	3.9-32	White	SKY1303WH	
	1300				Black	SKY1303BL	
T					Teak	SKY1303TK	
					White	SKY1503WH	
	1500	73/104/127/150/175/*88	322	3.9-43	Black	SKY1503BL	
					Teak	SKY1503TK	
NEW Skyfan DC 3 BLADE - Class II	1300	90/132/166/190/210/*110	244	3.9-32	White	SKY1303WHC2	


Ceiling	Skyfan DC 3 BLADE with LED	Sweep Dia. (mm)	LED (W)	Output (lm)	Fan Speed (RPM) 1, 2, 3, 4, 5, *ECO	Max Air Delivery (m³/min)	Wattage L-H (W)	Colour	Order Code						
	4	900			100/150/190/220/270/*120	208	3-32	White	SKY903WH-L						
	-	900			100/130/190/220/270/ 120	200	3-32	Black	SKY903BL-L						
		1000			05/140/170/000/000/*115	232	3.6-31	White	SKY1203WH-L						
		1200			95/140/170/200/230/*115	10 232	3.0-31	Black	SKY1203BL-L						
				1000	1000	1800	1800	1800	1800					White	SKY1303WH-L
		1300	20							90/132/166/190/210/*110	244	3.9-32	Black	SKY1303BL-L	
	•		20	1000				Teak	SKY1303TK-L						
	I							White	SKY1503WH-L						
-		1500			73/104/127/150/175/*88	322	3.9-43	Black	SKY1503BL-L						
ألمر									SKY1503TK-L						
	NEW/ Skyfan DC 3 BLADE with LED- Class II	1300			90/132/166/190/210/*110	244	3.9-32	White	SKY1303WHC2-L						

Skyfan DC 3 BLADE ACCESSORIES	Description	Order Code				
SE LE	LCD Wall Control	SKY	VCM			
	LCD Wall Control without Light	SKYWCM-2				
tuya	App Control	SKYAPPCM				
133.53	600/900/1200mm Extension Rods	White	Black			
	000/900/1200IIIII Exterision nous	SKYEXTR60/90/120WH	SKYEXTR60/90/120RI			

## Dimensions (mm)

204

Model	Α	В
SKY903	360	900
SKY1203	360	1200
SKY1303	360	1300
SKY1503	360	1500




SPYDA ceiling fans are a revolutionary design incorporating aerodynamic blades with true spin technology to produce increased air circulation with low power consumption. Blades are constructed of a precision moulded UV protected composite and highest quality Japanese silicon nitride bearings create a smooth running long life fan that is guaranteed to give years of trouble free operation. Ceiling fans are 220-240V AC, 50Hz operated and come complete with ECO airflow function and 3-speed fan controller. LED lights are 4 step dimmable with three selectable colours. 6 year warranty.

SPYDA 4 BLADE	Sweep Dia. (mm)	Fan Speed	Fan Rotation (RPM)	Air Delivery (m³/min)	Wattage (W)	Colour	Order Code
		Foonomy	107	101	14	White	SPY1254WH
	1050	Economy				Titanium	SPY1254TI
	1250	Medium	170	167	34	Teak	SPY1254TK
		High	230	210	55	Walnut	SPY1254WN
			SPYRFR5056				
						White	SPY1424WH
		Economy	100	105	13	Titanium	SPY1424TI
18	1400	Medium	140	174	22	Black	SPY1424BL
		High	220	222	68	Teak	SPY1424TK
54						Walnut	SPY1424WN
			3 Speed F	Remote Controll	ler		SPYRFR5056

SPYDA 4 BLADE with LED	Sweep Dia. (mm)	LED (W)	Output (Im)	Fan Speed	Fan Rotation (RPM)	Air Delivery (m³/min)	Fan Wattage (W)	Colour	Order Code
9								White	SPY1254WH-L
				Economy	107	101	14	Titanium	SPY1254TI-L
	1250	20	2050	Medium	170	167	34	Black	SPY1254BL-L
I				High	230	210	55	Teak	SPY1254TK-L
								Walnut	SPY1254WN-L
				3 Sp	eed Remote	e Controller			SPYRFR5056
								White	SPY1424WH-L
				Economy	100	105	13	Titanium	SPY1424TI-L
- T	1400	20	2050	Medium	140	174	22	Black	SPY1424BL-L
Ö				High	220	222	68	Teak	SPY1424TK-L
								Walnut	SPY1424WN-L
				3 Sp	eed Remote	e Controller			SPYRFR5056

SPYDA 4 BLADE	Description			Order Code	
ACCESSORIES	Description	Description		Titanium	Matte Black
		450mm	SPYEXTR45WH	SPYEXTR45TI	SPYEXTR45BL
	Extension Rods	600mm	SPYEXTR60WH	SPYEXTR60TI	SPYEXTR60BL
		900mm	SPYEXTR90WH	SPYEXTR90TI	SPYEXTR90BL
	Extension Rod Joiner Kits		SPJKWH	SPJKTI	SPJKBL
	J-Hook Hanging Packs		SPYJHWH	SPYJHTI	SPYJHBL

Model	A	В
SPY1254	330	1250
SPY1424	330	1400







SPYDA ceiling fans are a revolutionary design incorporating aerodynamic blades with true spin technology to produce increased air circulation with low power consumption. Blades are constructed of a precision moulded UV protected composite and highest quality Japanese silicon nitride bearings create a smooth running long life fan that is guaranteed to give years of trouble free operation. Ceiling fans are 220-240V AC, 50Hz operated and come complete with ECO airflow function and 3-speed fan controller. 6 year warranty.

SPYDA 3 BLADE	Sweep Dia. (mm)	Fan Speed	Fan Rotation (RPM)	Air Delivery (m³/min)	Wattage (W)	Colour	Order Code		
_		Economy	150	54	16	White	SPY903NWH		
<b>P</b>	900	Medium	210	75	24	Titanium	SPY903TI		
ä		High	280	95	60	Black	SPY903NBL		
			3 Speed F	Remote Control	ler		SSRFR36*		
						White	SPY1253NWH		
		_	407	404		Titanium	SPY1253NTI		
	1050	Economy	107	101	14	Black	SPY1253NBL		
(A)A	1250	Medium High	170 230	167	34 55	Bamboo	SPY1253NBAM		
ii a		riigii	230	210	33	Teak	SPY1253NTK		
-						Walnut	SPY1253NWN		
_			3 Speed F	Remote Control	ller		SPYRFR5056		
						White	SPY1423NWH		
		_	400		4.0	Titanium	SPY1423NTI		
			4.400		Economy	100	115	13	Black
Ö	1400		140	140 174 220 222	22 68	Bamboo	SPY1423NBAM		
-		High	220			Teak	SPY1423NTK		
						Walnut	SPY1423NWN		
			3 Speed F	Remote Control	ller		SPYRFR5056		
						White	SPY1573NWH		
•						Titanium	SPY1573NTI		
S		Economy	90	112	27	Black	SPY1573NBL		
_	1570	Medium	150	176	62	Bamboo	SPY1573NBAM		
		High	200	255	100	Teak	SPY1573NTK		
						Walnut	SPY1573NWN		
			3 Speed F	Remote Control	ler		SPYRFR62		


\*Please refer to Simx website - www.simx.co.nz for remote compatibility

				,		
SPYDA 3 BLADE	Description		Order Code			
ACCESSORIES	Description	Description		Titanium	Matte Black	
		450mm	SPYEXTR45WH	SPYEXTR45TI	SPYEXTR45BL	
	Extension Rods	600mm	SPYEXTR60WH	SPYEXTR60TI	SPYEXTR60BL	
		900mm	SPYEXTR90WH	SPYEXTR90TI	SPYEXTR90BL	
	Extension Rod Joiner	SPJKWH	SPJKTI	SPJKBL		
W.	J-Hook Hanging Packs		SPYJHWH	SPYJHTI	SPYJHBL	

#### Dimensions (mm)

206

Model	Α	В
SPY903N	330	900
SPY1253N	330	1250
SPY1423N	330	1400
SPY1573N	330	1570




SPYDA ceiling fans are a revolutionary design incorporating aerodynamic blades with true spin technology to produce increased air circulation with low power consumption. Blades are constructed of a precision moulded UV protected composite and highest quality Japanese silicon nitride bearings create a smooth running long life fan that is guaranteed to give years of trouble free operation. Ceiling fans are 220-240V AC, 50Hz operated and come complete with ECO airflow function and 3-speed fan controller. LED lights are 4 step dimmable with three selectable white colours. 6 year warranty.

SPYDA 3 BLADE with LED	Sweep Dia. (mm)	LED (W)	Output (Im)	Fan Speed	Fan Rotation (RPM)	Air Delivery (m³/min)	Fan Wattage (W)	Colour	Order Code
	000	20	2050	Economy Medium	150	54	16	White	SPY903WH-L
	900	20	2000	High	210 280	75 95	60	Titanium	SPY903TI-L
				3 Sp	eed Remote	e Controller			SSRFR36*
io -	1250	20	2050	Economy Medium High	107 170 230	101 167 210	14 34 55	White Titanium Black Bamboo Teak Walnut	SPY1253WH-L SPY1253TI-L SPY1253BL-L SPY1253BAM-L SPY1253TK-L SPY1253WN-L
				3 Sp	eed Remote	e Controller			SPYRFR5056
ä	1400	20	2050	Economy Medium High	100 140 220	115 174 222	13 22 68	White Titanium Black Bamboo Teak Walnut	SPY1423WH-L SPY1423TI-L SPY1423BL-L SPY1423BAM-L SPY1423TK-L SPY1423WN-L
				3 Sp	eed Remote	e Controller			SPYRFR5056
			2050	Economy	90	112	27	White Titanium Black	SPY1573WH-L SPY1573TI-L SPY1573BL-L
	1570	20		Medium High	150 200	176 255	62 100	Bamboo Teak Walnut	SPY1573BAM-L SPY1573TK-L SPY1573WN-L
				3 Sp	eed Remote	e Controller			SPYRFR62

	Theader to the commit website v	Trouble for to commit website www.ommx.co.mz for formette compatibility							
SPYDA 3 BLADE	Description	Description							
ACCESSORIES	Description		Satin White	Titanium	Matte Black				
	Extension Rods	450mm	SPYEXTR45WH	SPYEXTR45TI	SPYEXTR45BL				
<u> </u>		600mm	SPYEXTR60WH	SPYEXTR60TI	SPYEXTR60BL				
		900mm	SPYEXTR90WH	SPYEXTR90TI	SPYEXTR90BL				
	Extension Rod Joiner	Extension Rod Joiner Kits			SPJKBL				
W.	J-Hook Hanging Pac	ks	SPYJHWH	SPYJHTI	SPYJHBL				

	-	
Model	A	В
SPY1253	391	1250
SPY1423	393	1400
SPY1573	406	1570









SPINIKA ceiling fans are a revolutionary design incorporating aerodynamic blades with true spin technology to produce increased air circulation with low power consumption. Blades are constructed of a glass fibre composite and highest quality Japanese silicon nitride bearings create a smooth running long life fan that is guaranteed to give years of trouble free operation. Ceiling fans are 220-240V AC, 50Hz operated and come complete with ECO airflow function and 3-speed fan controller. LED lights are 4 step dimmable with three selectable white colours. 6 year warranty.


SPINIKA 4 BLADE	Sweep Dia. (mm)	Fan Speed	Fan Rotation (RPM)	Air Delivery (m³/min)	Wattage (W)	Colour	Order Code									
100	1000	Economy Medium	100 160	84 133	20 23	White	SPIN1204WH									
	1220	High	220	208	60	Titanium	SPN1204TI									
Ф			SPNRFR													
		Economy	100	108	20	White	SPIN1304WH									
	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300	Medium	160	174	38	Titanium	SPN1304TI
	High	220	250	65	Black	SPN1304BL										
-			3 Speed	Remote Contro	ller		SPNRFR									

SPINIKA 4 BLADE with LED	Sweep Dia. (mm)	LED (W)	Output (lm)	Fan Speed	Fan Rotation (RPM)	Air Delivery (m³/min)	Fan Wattage (W)	Colour	Order Code
- 9				Economy	100	101	20	White	SPIN1204WH-L
		20	2050	Medium	160	167	167 23 210 60	Titanium	SPIN1204TI-L
				High	220	210		Black	SPN1204BL-L
\ I_				3 Sp	eed Remote	Controller			SPNRFR
				Economy	100	105	20	White	SPN1304WH-L
	1300	0 20 2050 Medium 160 174	0 2050	174	174 38	Titanium	SPN1304TI-L		
				High	220	222	65	Black	SPN1304BL-L
				3 Sp	eed Remote	Controller			SPNRFR

SPINIKA 4 BLADE	Description		Order Code				
ACCESSORIES	Description		Satin White	Titanium	Matte Black		
	Extension Rods	600mm	SPNEXTR60WH	SPNEXTR60TI	SPNEXTR60BL		
	Extension hous	900mm	SPNEXTR90WH	SPNEXTR90TI	SPNEXTR90BL		
A	Extension Rod Joiner	Kits	SPJKWH	SPJKTI	SPJKBL		
	J-Hook Hanging Pag	cks	SPYJHWH	SPYJHTI	SPYJHBL		
Alt-							

### **Dimensions (mm)**

Model	A	В
SPN1204	360	1220
SPN1204-L	392	1220
SPN1304	360	1300
SPN1304-L	392	1300






STANZA ceiling fans features True-spin Technology™ and is the latest development in ceiling fan motor engineering. The Precision moulded glass fibre composite blades for increased stability and higher airflow, are individually balance tested and quality checked for trouble free operation. A pre-selected speed ECO switch setting allows the fan to run at a reduced running cost whilst maintaining adequate air circulation, which is also suitable for gentle heat circulation in winter. Available with or without B22 light fitting. Ceiling fans are 220-240V AC, 50Hz operated and come complete with ECO airflow function. Suitable for indoor and covered outdoor areas. 4 year warranty.

STANZA 3 BLADE	Sweep Dia. (mm)	Fan Speed	Fan Rotation (RPM)	Max Air Delivery (m³/min)	Wattage L-H (W)	Colour	Order Code
Ö	1220	Economy Medium High	105 150 190	- - 195	17 35 55	White	STA1203WH
				STARFR48			

STANZA 3 BLADE with LIGHT	Sweep Dia. (mm)	Light Type	Light Wattage (W)	Fan Rotation (RPM)	Max Air Delivery (m³/min)	Wattage L-H (W)	Colour	Order Code
Ö	1220	B22 Lamp Holder	2 x 15W	105 150 190	- - 195	17 35 55	White	STA1203WH-L
10000		3 Speed Remote Controller						STARFR48

STANZA 3 BLADE	Description		Order Code				
ACCESSORIES	Description		Satin White	Titanium	Matte Black		
	Extension Rods	600mm	SPNEXTR60WH	SPNEXTR60TI	SPNEXTR60BL		
	EYIGHAINH DOOS	900mm	SPNEXTR90WH	SPNEXTR90TI	SPNEXTR90BL		
No	Extension Rod Joiner	Kits	SPJKWH	SPJKTI	SPJKBL		
	J-Hook Hanging Pac	ks	SPYJHWH	SPYJHTI	SPYJHBL		

Model	Α	В
STA1203	349	1220
STA1203-L	399	1220



ROYALE II DC and SEATTLE DC ceiling fans are the latest in energy saving DC technology using up to 50-75% less power than comparable AC operated fans with similar performance levels. All fans incorporate precision moulded ABS blades which are pre-balanced for smoother, quieter performance. Reversible function is available on the 5-speed remote controller with timer included. Fans are 220-240V AC, 50Hz operated and come complete with ECO airflow function. Suitable for indoor and covered outdoor areas. 6 year warranty.

ROYALE II DC 4 BLADE	Sweep Dia. (mm)	Fan Speed	Fan Rotation (RPM)	Wattage (W)	Colour	Order Code
		1	105			
	1320	2	145		White	ROY1304WH-DC
\ I		3	180	4-33		
		4	210			
		5	245			


ROYALE II DC 4 BLADE with LED	Sweep Dia. (mm)	LED (W)	Output (Im)	LED Colour	Fan Speed	Fan Rotation (RPM)	Fan Wattage (W)	Colour	Order Code
					1	105			
					2	145			
	1320	18	1500	4000K	3	180	4-33	White	ROY1304WHL-DC
					4	210			
					5	245			

SEATTLE DC 3 BLADE	Sweep Dia. (mm)	Fan Speed	Fan Rotation (RPM)	Wattage (W)	Colour	Order Code
		1	86			
		2	120			
1	1400	3	161	5-38	Light Oak	SEA1403LO-DC
		4	186			
		5	206			

ACCESSORIES	Description	Fan	Colour	Order Code
	Extension Rods	Royale II DC	White	HRMXR90-WH-DC
	900mm	Seattle DC	Black	SEAWASXR90-BL
	Pitched Ceiling/Extension Rod Canopy	Seattle DC	Black	NGCANOPYBL

## Dimensions (mm)

Model	A	В
R0Y1304-DC	335	1320
ROY1304L-DC	373	1320
SEA1403	385	1400



MARIAH ceiling fan is a new generation design offering the latest in fan technology. Incorporating five precision moulded ABS blades and a premium long life motor, this fan provides excellent air circulation and cooling.

MALIBU IP55 ceiling fan is designed specifically for outdoor and coastal applications. Incorporating four durable moulded ABS blades and a premium long life motor, this fan is engineered for large area air circulation providing up to 50% more air circulation than timber blade fans. NATIONAL ceiling fan is designed specifically for covered outdoor and coastal area applications. Incorporating four 316 stainless steel marine grade blades and a premium long life ball bearing motor, this fan provides excellent air circulation and cooling.

Blades for all fans are pre-balanced for smoother, quieter performance and a reversible airflow option for summer or winter is available. Fans are 220-240V AC, 50Hz operated. 6 year warranty.


MARIAH 5 BLADE with LED	Sweep Dia. (mm)	LED (W)	Output (lm)	LED Colour	Fan Speed	Fan Rotation (RPM)	Fan Wattage (W)	Colour	Order Code
	1320	18	1500	4000K	1 2 3	110 165 240	75	White	MAR1305WH-L
0 -			3 Speed I	Remote Co	ontroller wi	th 1-9 hr Ti	mer Functi	on	NGCFRC

MALIBU IP55 4 BLADE	Sweep Dia. (mm)	Fan Speed	Fan Rotation (RPM)	Wattage (W)	Colour	Order Code
ALL WEATHER DESIGNED FOR THE OUTDOORS	1320	1 2 3	104 161 255	100	Titanium	MAL1404TI
		3 Speed Rem	ote Controller with	n 1-9 hr Time	er Function	NGCFRC

NATIONAL 4 BLADE	Sweep Dia. (mm)	Fan Speed	Fan Rotation (RPM)	Wattage (W)	Colour	Order Code
CALL WEATHER DESIGNED FOR THE OUTDOORS	1320	1 2 3	80 130 230	75	Stainless Steel	Z524EXTSS
			3 Speed Remote	Controller		VRFR


ACCESSORIES	Description		Fan	Colour	Order Code
			Mariah	White	MARXR90-WH
	Extension Rods	900mm	Malibu IP55	Titanium	HRMXR90-TI
			National	Stainless Steel	VEXRS316900

Model	Α	В
MAR1305	308	1320
MAR1305-L	375	1320
MAL1404	355	1320
Z524	340	1320





ZEPHYR II Wall mount fan	Fan Size (mm)	Grille Size (mm)	Fan Wattage (W)	Fan Mode	Fan Rotation (RPM)	Colour	Switching	Order Code
	400	450	65	Sleep Breeze	950 1150	White	Pull Cord	ZEP40PC
	400	450	03	Wind	1300	wille	Remote	ZEP40R



ORBITAL is a commercial grade ceiling mount cooling fan with a wall switch included. 360° orbital motion ensures maximum cooling is

achieved Ideal for warmer climates, this fan, with 3 speed settings delivers high airflow at low noise level. 2 year warranty.

213

## **Cooling Fans**



**Wall Cooling Fans** are heavy duty fans with oscillating and tilt adjustable heads. New anti-vibration patented blade design ensures that high airflows delivered are at a very low noise level. Pedestal fans also feature an adjustable head height. 2 year warranty.

WALL COOLING FAN	Fan Size (mm)	Grille Size (mm)	Fan Wattage (W)	Fan Mode	Fan Rotation (RPM)	Colour	Switching	Order Code
	450	515	160	1 2 3	1100 1300 1400	Black	Pull Cord	WAL45
	750	815	130	1 2 3 4 5	600 700 800 900 1000 1035	Black	Six Speed Remote Control	WAL75-DC



