


## PD 360/24 BASIC IP54

**Item number**      **GTIN**  
 EB10431289      4015120431289



### Technical data

GENERAL	
Device category	Ceiling-mounted presence detector
Product information	Please note the Explanation of circuit breaker in the download area of the product!
User interface	Adjusting controller
Remote controllable	–
Conformity	CE, EAC, RoHS, WEEE
Product-specific information	Lens mask and spacer not included in delivery
Warranty	5 years
ATTACHMENT	
Installation type	Surface mounting
Installation position	Ceiling
Type of connection	Screwed terminal
Connectable wire cross section	0.75 – 2.50 mm <sup>2</sup>
HOUSING	
Dimensions	Height/Depth 71 mm, Ø 102 mm
Weight	145 g
Material	UV-stabilised polycarbonate
Protection type	IP54
Permissible ambient temperature	0 °C...+50 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9010
ELECTRICAL VERSION	
Control system	ON/OFF
Protection class	II
Nominal voltage	230 V ~ / 50 - 60 Hz

### Product description

- Ceiling-mounted presence detector with 360° field of detection
- Automatic light control depending on presence and daylight
- Range of up to 24 m in diameter at a recommended installation height of 3 m
- Protection type: IP54
- 10 A high-performance relay
- Protective zero-cross switching: extension of the lifetime of the relay and illuminants using electronic ballasts (e.g. fluorescent lamps, LEDs)
- Factory settings for immediate operational readiness
- Additional switch input
- Sensing range upgrade through parallel connection

### Offers special product features like:

- Zero-cross switching

In-rush current	78 A / 5 ms
Power consumption	0.2 W

### SENSORS

Detection angle	360°
Detection range diagonally	Ø 24 m
Detection range head-on	Ø 8 m
Detection range presence	Ø 8 m
Field of detection	up to 453 m <sup>2</sup>
Range adjustment	mechanically with included cut to size lens mask
Recommended installation height	3 m
Max. mounting height	5 m
Light measurement	mixed light
Level of brightness	5–2000 lx

### CHANNELS (LIGHTING / HVAC)

Number of light channels	1
Push button input lighting	1
Push button input HVAC	–
Number of parallel switchable detectors	8
Slave input	–
Mode	Fully automatic
Switching delay from "dark to light"	300 s
Switching delay from "light to dark"	30 s
Constant light control	–
Channel	C1 Lighting
Function	Switching
Switching capacity	230 V/50 Hz 2300 W/10 A (cos phi = 1)

# DATA SHEET

## PD 360/24 BASIC IP54

Item number	GTIN
EB10431289	4015120431289

	1150 VA/5 A (cos phi = 0,5) 600 W LED
Switch contact	make contact / non-floating

Push button input	✓
Impulse mode	✓
Switch-off delay time	15 s...30 min (adjustable in steps)

### Factory settings


Channel	C1 Lighting
Level of brightness/switching threshold	500 lx

Switch-off delay time	5 min
-----------------------	-------


### Accessories

Product designation	Item number	Product description	GTIN
<b>Cover</b>			
BASIC IP54 24 LENS MASK	EB10423505	Spare part Lens mask 24 m IP54	4015120423505
<b>Protection</b>			
BASKET GUARD ROUND LARGE	EM10425608	Basket guard for presence and motion detectors and smoke detectors, Ø 180 mm, height 90 mm	4015120425608

### Dimension drawing



### Field of detections



### Detection range


Diagonally (A)	Ø 24 m
Frontal (B)	Ø 8 m
Presence area (C)	Ø 8 m

## PD 360/24 BASIC IP54

**Item number**      **GTIN**  
EB10431289      4015120431289

### Circuit diagram

---



---

*Standard operation*

### Detailed product description

---

- Ceiling-mounted presence detector with 360° field of detection
- Automatic light control depending on presence and daylight
- Range of up to 24 m in diameter at a recommended installation height of 3 m
- Protection type: IP54
- 10 A high-performance relay
- Protective zero-cross switching: extension of the lifetime of the relay and illuminants using electronic ballasts (e.g. fluorescent lamps, LEDs)
- Factory settings for immediate operational readiness
- Additional switch input
- Sensing range upgrade through parallel connection