

ELSA-2 DL 225 OP 110° 1800 840 WH

Item number E010299018
GTIN 4015120299018

ON/OFF	220 - 240 V ~/~	LED 4000 K	CRI 81	Phi 1800 lm	100 lm/W	UGR ≤ 25
IP20 IP44						



Technical data

GENERAL	
Device category	Downlight
Product information	Do not cover the downlight directly with insulating material.
Remote controllable	-
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years
ATTACHMENT	
Installation type	Recessed mounting
Installation position	Ceiling
Installation dimension	Installation depth: 40 mm, Ø 225 mm
Type of connection	Open end
Connectable wire cross section	0.75 - 2.5 mm ²
Number of contacts	3
Length of cable	0.18 m
HOUSING	
Dimensions	Height 25 mm, Ø 240 mm
Weight	873 g
Material	powder-coated aluminium
Protection type	IP20 / IP44 below the ceiling (built-in)
Permissible ambient temperature	-20 °C...+40 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9003
Glow wire test in accordance with IEC 60695-2-10	650 °C

Product description

- LED downlight, 4000K with opal cover (diffuser), 18W, for ceiling mounting without additional accessories
- High light quality and system performance
- Operating device on/off, included

ELECTRICAL VERSION	
Control system	ON/OFF
Protection class	II
Nominal voltage	220 - 240 V AC/DC / 50 - 60 Hz
LIGHT	
Diffuser	opal
Light emission	direct
Beam angle	110 °
Unified Glare Rating	≤ 25
Flicker factor	0 %
Rated output P	18 W
Luminous flux - min	1800 lm
Luminous flux - max	1800 lm
Luminous efficacy - min	100 lm/w
Luminous efficacy - max	100 lm/w
Colour temperature	4000 K
Colour rendering index Ra	> 80
Colour tolerance	1SDCM
Color Quality Scale	>80
L70B10 lifetime at 25 °C	60000 h
Life time L70B50 at 25 °C	60000 h
Life time L80B10 at 25 °C	40000 h
Life time L80B50 at 25 °C *	40000 h
Life time L90B10 at 25 °C	20000 h
Life time L90B50 at 25 °C	20000 h
Photobiological safety	RG0


ELSA-2 DL 225 OP 110° 1800 840 WH

Item number	GTIN
EO10299018	4015120299018


Accessories

Product designation	Item number	Product description	GTIN
Adapter			
ELSA-2 RING 225	EO10300264	Adapter ring 225-265 mm for ELSA-2 series	4015120300264
Electrical accessories			
JUNCTION BOX 5-POLE BK	EO10430992	Universal junction box, black, 5-pin, 2.5 mm ²	4015120430992
Mounting			
ELSA-2 MOUNTING FRAME 225 SM WH	EO10300899	Ceiling installation frame for ELSA-2 225 series	4015120300899


Dimension drawing



Lichtverteilung



Circuit diagram



Standard operation.

Detailed product description

- LED downlight, 18 W for ceiling mounting
- Recessed luminaire with opal cover (diffuser)
- High-quality housing, aluminium lamp body, white powder-coated (RAL 9003)
- Can be used for ceiling mounting without additional accessories
- Colour temperature: 4000 K with the lowest colour tolerances
- Luminous flux: 1750 lm

DATA SHEET



ELSA-2 DL 225 OP 110° 1800 840 WH

Item number	GTIN
EO10299018	4015120299018

- High light quality
- Excellent system efficiency
- Life time L80B50 at 25 °C*: 40000 h
- Operating device: on/off (included)