

PD-C 360/8 mini BMS DALI-2

Item number **GTIN**
 EP10423048 4015120423048



Technical data

GENERAL	
Device category	Ceiling-mounted presence detector
User interface	DALI-Bus
Remote controllable	–
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years
ATTACHMENT	
Installation type	Recessed mounting
Installation position	Ceiling
Installation dimension	Installation depth: 45 mm, Ø 25 mm
Type of connection	Open end
Connectable wire cross section	0.60 – 0.80 mm ²
HOUSING	
Dimensions	Height/Depth 60 mm, Ø 33 mm
Weight	24 g
Material	UV-stabilised PE
Protection type	IP55
Permissible ambient temperature	-25 °C...+50 °C
Relative humidity	5 - 95 %, non-condensing
Colour	opal matt
ELECTRICAL VERSION	
Control system	DALI-2
Protection class	III
Nominal voltage	9.5–22.5 V DC

Product description

- DALI-2-certified BMS ceiling-mounted presence detector with 360° field of detection
- Range of up to 8 m in diameter at a recommended installation height of 3 m
- Input device with integrated PIR sensor and light sensor for DALI-2 commands in line with IEC 62386-303/304
- For decentralised light control in combination with APC presence detectors with integrated control unit
- Alternative: simple integration into third-party building management systems
- Interoperability in accordance with DALI-2 standard

No load current DALI	6 mA
Peak current DALI	12 mA

SENSORS

Detection angle	360°
Detection range diagonally	Ø 8 m
Detection range head-on	Ø 5 m
Detection range presence	Ø 3 m
Field of detection	up to 45 m ²
Recommended installation height	3 m
Max. mounting height	3 m
Light measurement	mixed light
Level of brightness	10–2000 lx

CHANNELS (LIGHTING / HVAC)

Number of light groups	16
Push button input HVAC	–
Slave input	–
Constant light control	–
DALI-2 device type	Input device in accordance with -303 (presence and motion detectors), Input device in accordance with -304 (light sensor)
Switch-on time	600 ms
Channel	C1 Lighting
Function	Send values
Switch contact	Bus system
Push button input	–
Impulse mode	–

PD-C 360/8 mini BMS DALI-2

Item number	GTIN
EP10423048	4015120423048

Factory settings

GENERAL	
Sensitivity	100 %

Accessories

Product designation	Item number	Product description	GTIN
Adapter			
COMPACT MINI SPOTLIGHT ADAPTER 51/25	EP10426391	Adapter for COMPACT MINI (8 m and 12 m) series for installing motion and presence detectors in spotlights (illuminant size QR-CBC51-Ø 51 mm) with retaining ring	4015120426391

Field of detections	Detection range	Circuit diagram
	<ul style="list-style-type: none"> Diagonally (A) Ø 8 m 	
	<ul style="list-style-type: none"> Frontal (B) Ø 5 m 	
	<ul style="list-style-type: none"> Presence area (C) Ø 3 m 	

Standard operation

Detailed product description

- DALI-2-certified BMS ceiling-mounted presence detector with 360° field of detection
- Range of up to 8 m in diameter at a recommended installation height of 3 m
- Input device with integrated PIR sensor and light sensor for DALI-2 commands in line with IEC 62386-303/304
- For decentralised light control in combination with APC presence detectors with integrated control unit
- Alternative: simple integration into third-party building management systems
- Interoperability in accordance with DALI-2 standard